



A NEW GENERATION OF SMOOTH, PVC-FREE FLOORING

Technologically advanced barenaked PVC free floors have been designed particularly for public spaces that are exposed to especially high wear. Besides their durable structure and easy maintenance, barenaked PVC free products are completely free from PVC and plasticizers. Thus, they are exceptionally safe - both for the users and the environment.

CS is the flagship of the product family. Its 48 color options have been fully synchronized, providing plenty of opportunities to design a personal space with a feeling that fully complements its usage.

- » Completely free of PVC and plasticizers
- » No wax required
- » Fully flexible
- » Excellent stain resistance
- » Bacteria resistant and anti-static
- » Contains over 25 % pre consumer recycled content



TECHNICAL DATA EN 14565

Thickness	0.08" (2.0 mm)
Roll Length (typical)	82' (25 m)
Roll Width	4'9" (1.45 m)
Weight	0.61 lbs/Sq. ft (3.2 kg/m ²)
Warranty	15 years
Static Load Limit ASTM 970	2000 PSI
Critical Radiant Flux ASTM E648	≥ 0.45 w/cm ²
Smoke Generation ASTM E662	<450 DM Corrected
Taber Abrasion ASTM C501	Pass
Pre Consumer Recycled Content	>25 %
VOC Emissions CA 01350	Very Low Emitting Material, FloorScore certified SCS-FS-02256
Wear resistance EN 660-2	T (Best)
Critical Radiant Flux ASTM E648	Class I
Smoke Density ASTM E662	<450 DM Corrected
Chemical Resistance ASTM F925	Pass
Static Coefficient Of Friction ASTM C1028	0.6 SCOF Complies with ADA Guidelines



ADDITIONAL ASTM STANDARDS

Static Load Limit ASTM F970	2000 psi
Fire Resistance ASTM E648-08	Class 1
Smoke Density ASTM E662 -03	<450
Resistance to chemicals ASTM F925	Pass
Static Coefficient of Friction ASTM C1028	Pass
Thickness of Resilience ASTM F386	Pass
Impact Resistance ASTM F1265	Pass
Dimensional Stability ASTM F2199	Pass
Heat Stability by Color Change ASTM F1514	Pass
Short-term Indentation Resistance ASTM F1914	Pass
Indoor Air Quality CA 01350	Pass



Shannon Specialty Floors, Inc.
1005 South 60th St.
Milwaukee, WI 53214
Toll Free: 800.522.9166
Phone: 414.771.9166